

SAFETY DATA SHEET

EASTMAN

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758

Skydrol® LD4 Fire Resistant Hydraulic Fluid

Customer PO: POR0113258

Version	Revision Date:	SDS Number:	Date of last issue: 06.08.2020
2.6	05.01.2023	150000093409	Date of first issue: 18.09.2013
PRD		SDSGB / EN / 0279	J56 / 0091658533 / 0001008286

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Skydrol® LD4 Fire Resistant Hydraulic Fluid

Product code : P3410206

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-
stance/Mixture : Hydraulic fluids

Recommended restrictions
on use : None known.

1.3 Details of the supplier of the safety data sheet

Company : Solutia U.K. Limited
A Subsidiary of Eastman Chemical Company
Corporation Road
NP19 4XF Newport, South Wales

E-mail address of person
responsible for the SDS : Visit our website at www.EASTMAN.com or email
emnmsds@eastman.com

1.4 Emergency telephone number

Tel. 111

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

**Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK
SI 2019/720, and UK SI 2020/1567)**

Skin irritation, Category 2 H315: Causes skin irritation.

Carcinogenicity, Category 2 H351: Suspected of causing cancer.

Long-term (chronic) aquatic hazard, Cat-
egory 3 H412: Harmful to aquatic life with long lasting ef-
fects.

2.2 Label elements

**Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI
2019/720, and UK SI 2020/1567)**

SAFETY DATA SHEET

EASTMAN

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758

Skydrol® LD4 Fire Resistant Hydraulic Fluid

Customer PO: POR0113258

Version	Revision Date:	SDS Number:	Date of last issue: 06.08.2020
2.6	05.01.2023	150000093409	Date of first issue: 18.09.2013
PRD		SDSGB / EN / 0279	J56 / 0091658533 / 0001008286

Hazard pictograms :



Signal word : Warning

Hazard statements : H315 Causes skin irritation.
H351 Suspected of causing cancer.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements :

Prevention:

P201 Obtain special instructions before use.
P264 Wash skin thoroughly after handling.
P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

Response:

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Hazardous components which must be listed on the label:

Tributyl phosphate

Additional Labelling

EUH208 Contains 7-Oxabicyclo[4.1.0]heptane-3-carboxylic acid, 2-ethylhexyl ester.
May produce an allergic reaction.

EUH208 Contains 7-Oxabicyclo[4.1.0]heptane-3-carboxylic acid, 2-ethylhexyl ester.
May produce an allergic reaction.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)

SAFETY DATA SHEET

EASTMAN

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758

Skydrol® LD4 Fire Resistant Hydraulic Fluid

Customer PO: POR0113258

Version	Revision Date:	SDS Number:	Date of last issue: 06.08.2020
2.6	05.01.2023	150000093409	Date of first issue: 18.09.2013
PRD		SDSGB / EN / 0279	J56 / 0091658533 / 0001008286

Tributyl phosphate	126-73-8 204-800-2 015-014-00-2 01-2119492859-14- 0002, 01- 2119967407-27- 0000	Acute Tox. 4; H302 Skin Irrit. 2; H315 Carc. 2; H351 Aquatic Chronic 3; H412	>= 50 - < 70
Reaction mass of butyl diphenyl phosphate and dibutyl phenyl phosphate and tributyl phosphate	Not Assigned 907-672-2	Carc. 2; H351 Aquatic Chronic 3; H412	>= 20 - < 25
7-Oxabicyclo[4.1.0]heptane-3-carboxylic acid, 2-ethylhexyl ester	62256-00-2 263-471-3 01-2120767056-51- xxxx	Skin Sens. 1; H317	>= 1 - < 10
butylated hydroxytoluene	128-37-0 204-881-4 01-2119565113-46- xxxx	Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	>= 1 - < 2.5

For explanation of abbreviations see section 16.

Eastman is committed to the safety, health and environment of our employees, our customers, and the communities we operate within. As part of this commitment, Eastman's Safety Data Sheets (SDS) are prepared in accordance with all applicable national and local regulations. The compositions of our documents reflect these requirements which include, but are not limited to, requirements under the Globally Harmonized System of Classification and Labeling (GHS). These compositions commonly involve the use of ranges versus specific analytical values. If you require a composition that is more specific, please refer to the Certificate of Analysis, sales specification, or contact your Customer Service Representative.

SECTION 4: First aid measures

4.1 Description of first aid measures

- If inhaled : Move to fresh air.
If breathing is difficult, give oxygen.
Consult a physician if necessary.
- In case of skin contact : Wash off immediately with plenty of water for at least 15 minutes.
Get medical attention if symptoms occur.
Wash contaminated clothing before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
Get medical attention if symptoms occur.

SAFETY DATA SHEET

EASTMAN

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758

Skydrol® LD4 Fire Resistant Hydraulic Fluid

Customer PO: POR0113258

Version	Revision Date:	SDS Number:	Date of last issue: 06.08.2020
2.6	05.01.2023	150000093409	Date of first issue: 18.09.2013
PRD		SDSGB / EN / 0279	J56 / 0091658533 / 0001008286

If swallowed : Call a physician or poison control center immediately.
Do not induce vomiting without medical advice.
Rinse mouth.
Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Risks : Causes skin irritation.
Suspected of causing cancer.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray
Carbon dioxide (CO₂)
Dry chemical
Foam

Unsuitable extinguishing media : Do not use a solid water stream as it may scatter and spread fire.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products : Carbon monoxide
Carbon dioxide (CO₂)
oxides of phosphorus

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear an approved positive pressure self-contained breathing apparatus in addition to standard fire fighting gear.

Further information : Use a water spray to cool fully closed containers.
Do not allow run-off from fire fighting to enter drains or water courses.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Ventilate the area.
Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
Avoid contact with skin and eyes.
Material can create slippery conditions.
Wear appropriate personal protective equipment.
Local authorities should be advised if significant spillages

SAFETY DATA SHEET

EASTMAN

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758

Skydrol® LD4 Fire Resistant Hydraulic Fluid

Customer PO: POR0113258

Version	Revision Date:	SDS Number:	Date of last issue: 06.08.2020
2.6	05.01.2023	150000093409	Date of first issue: 18.09.2013
PRD		SDSGB / EN / 0279	J56 / 0091658533 / 0001008286

cannot be contained.

6.2 Environmental precautions

Environmental precautions : Clear up spills immediately and dispose of waste safely.
Avoid release to the environment.
Collect spillage.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Do not breathe vapors or spray mist.
Handle product only in closed system or provide appropriate exhaust ventilation at machinery.
In case of insufficient ventilation, wear suitable respiratory equipment.
Wear appropriate personal protective equipment.
Avoid contact with skin, eyes and clothing.
Wash thoroughly after handling.
Wash contaminated clothing before reuse.
Drain or remove substance from equipment prior to break-in or maintenance.
Handle in accordance with good industrial hygiene and safety practice.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store locked up. Keep container tightly closed in a dry and well-ventilated place. Keep in a cool place away from oxidizing agents.

7.3 Specific end use(s)

Specific use(s) : www.EastmanAviationSolutions.com

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

SAFETY DATA SHEET

EASTMAN

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758

Skydrol® LD4 Fire Resistant Hydraulic Fluid

Customer PO: POR0113258

Version	Revision Date:	SDS Number:	Date of last issue: 06.08.2020
2.6	05.01.2023	150000093409	Date of first issue: 18.09.2013
PRD		SDSGB / EN / 0279	J56 / 0091658533 / 0001008286

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Tributyl phosphate	126-73-8	TWA	5 mg/m ³	GB EH40
		STEL	5 mg/m ³	GB EH40
butylated hydroxy-toluene	128-37-0	TWA	10 mg/m ³	GB EH40

Derived No Effect Level (DNEL):

Substance name	End Use	Exposure routes	Potential health effects	Value
7-Oxabicyclo[4.1.0]heptane-3-carboxylic acid, 2-ethylhexyl ester	Workers	Inhalation	Long-term systemic effects	1.03 mg/m ³
	General Population	Inhalation	Long-term systemic effects	0.25 mg/m ³
	General Population	Oral	Long-term systemic effects	0.58 mg/kg bw/day

Predicted No Effect Concentration (PNEC):

Substance name	Environmental Compartment	Value
7-Oxabicyclo[4.1.0]heptane-3-carboxylic acid, 2-ethylhexyl ester	Fresh water	0.0026 mg/l
	Marine water	0.00026 mg/l
	Fresh water sediment	1.18 mg/kg
	Marine sediment	0.118 mg/kg
	Sewage treatment plant	10 mg/l
	Soil	0.235 mg/kg

8.2 Exposure controls

Engineering measures

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Personal protective equipment

Eye/face protection : Wear safety glasses with side shields (or goggles).

Hand protection

Remarks : Wear suitable gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. After contamination with product change the gloves immediately and dispose of them according to relevant national and local regulations.

SAFETY DATA SHEET

EASTMAN

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758

Skydrol® LD4 Fire Resistant Hydraulic Fluid

Customer PO: POR0113258

Version	Revision Date:	SDS Number:	Date of last issue: 06.08.2020
2.6	05.01.2023	150000093409	Date of first issue: 18.09.2013
PRD		SDSGB / EN / 0279	J56 / 0091658533 / 0001008286

- Skin and body protection : Wear suitable protective clothing.
- Respiratory protection : Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary.
Respirator selection, use, and maintenance must be in accordance with regulatory requirements, if applicable.
If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.
- Protective measures : Ensure that eye flushing systems and safety showers are located close to the working place.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- Appearance : oily
- Colour : purple
- Odour : odourless
- Odour Threshold : not determined
- pH : No data available
- Melting point/range : < -62 °C
- Boiling point/boiling range : not determined
- Flash point : 174 °C
Method: Cleveland open cup
- Evaporation rate : not determined
- Upper explosion limit / Upper flammability limit : not determined
- Lower explosion limit / Lower flammability limit : not determined
- Vapour pressure : 0.27 hPa (25 °C)
- Relative vapour density : not determined
- Relative density : 1.0111 (25 °C)
- Partition coefficient: n- : No data available

SAFETY DATA SHEET

EASTMAN

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758

Skydrol® LD4 Fire Resistant Hydraulic Fluid

Customer PO: POR0113258

Version	Revision Date:	SDS Number:	Date of last issue: 06.08.2020
2.6	05.01.2023	150000093409	Date of first issue: 18.09.2013
PRD		SDSGB / EN / 0279	J56 / 0091658533 / 0001008286

octanol/water

Auto-ignition temperature : 469 °C
Method: ASTM D2155

Decomposition temperature : not determined

Viscosity

Viscosity, dynamic : not determined

Viscosity, kinematic : < 2000 mm²/s (-54 °C)

11.15 mm²/s (38 °C)

3.83 mm²/s (99 °C)

Explosive properties : No data available

Oxidizing properties : No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

None reasonably foreseeable.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : None known.

10.4 Conditions to avoid

Conditions to avoid : None known.

10.5 Incompatible materials

Materials to avoid : Strong oxidizing agents

10.6 Hazardous decomposition products

Emits acrid smoke and fumes when heated to decomposition.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information.

SAFETY DATA SHEET

EASTMAN

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758

Skydrol® LD4 Fire Resistant Hydraulic Fluid

Customer PO: POR0113258

Version	Revision Date:	SDS Number:	Date of last issue: 06.08.2020
2.6	05.01.2023	150000093409	Date of first issue: 18.09.2013
PRD		SDSGB / EN / 0279	J56 / 0091658533 / 0001008286

Product:

Acute oral toxicity : LD50 (Rat, male and female): 2,100 mg/kg

Acute inhalation toxicity : LC50 (Rat, male): > 5.8 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: (highest concentration tested)

Acute dermal toxicity : LD50 Dermal (Rabbit, male and female): > 3,160 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

Components:

Tributyl phosphate:

Acute oral toxicity : LD50 Oral (Rat, male and female): 1,553 mg/kg
Assessment: Harmful if swallowed.

LD50 Oral (Rat, male and female): 1,400 mg/kg

Acute inhalation toxicity : LC50 (Rat, male and female): > 4.242 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 Dermal (Rabbit, male and female): > 3,100 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

Reaction mass of butyl diphenyl phosphate and dibutyl phenyl phosphate and tributyl phosphate:

Acute oral toxicity : Acute toxicity estimate (Rat, male and female): 2,400 - 3,000 mg/kg
Assessment: Not classified

Acute inhalation toxicity : LCLo (Rat, male and female): > 5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity

LC50 (Rat, male and female): > 5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: Not classified

Acute dermal toxicity : LD50 Dermal (Rabbit, male and female): > 5,000 mg/kg
Assessment: Not classified

SAFETY DATA SHEET

EASTMAN

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758

Skydrol® LD4 Fire Resistant Hydraulic Fluid

Customer PO: POR0113258

Version	Revision Date:	SDS Number:	Date of last issue: 06.08.2020
2.6	05.01.2023	150000093409	Date of first issue: 18.09.2013
PRD		SDSGB / EN / 0279	J56 / 0091658533 / 0001008286

7-Oxabicyclo[4.1.0]heptane-3-carboxylic acid, 2-ethylhexyl ester:

Acute oral toxicity : LD50 Oral (Rat, male and female): 4,470 mg/kg
Acute dermal toxicity : LD50 Dermal (Rabbit, male and female): > 7,940 mg/kg

butylated hydroxytoluene:

Acute oral toxicity : LD50 Oral (Rat): > 6,000 mg/kg
Acute dermal toxicity : LD50 Dermal (Guinea pig): > 20,000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Product:

Species : Rabbit
Exposure time : 24 h
Assessment : irritating
Result : moderate irritation

Components:

Tributyl phosphate:

Species : Rabbit
Exposure time : 4 h
Assessment : Causes skin irritation.
Result : irritating

Reaction mass of butyl diphenyl phosphate and dibutyl phenyl phosphate and tributyl phosphate:

Species : Rabbit
Assessment : Not classified
Result : none

Species : Humans
Exposure time : 24 h
Assessment : Not classified
Result : none

7-Oxabicyclo[4.1.0]heptane-3-carboxylic acid, 2-ethylhexyl ester:

Species : Rabbit
Exposure time : 24 h
Assessment : Not classified as hazardous.
Result : slight to moderate irritation

butylated hydroxytoluene:

Species : Rabbit
Exposure time : 24 h

SAFETY DATA SHEET

EASTMAN

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758

Skydrol® LD4 Fire Resistant Hydraulic Fluid

Customer PO: POR0113258

Version	Revision Date:	SDS Number:	Date of last issue: 06.08.2020
2.6	05.01.2023	150000093409	Date of first issue: 18.09.2013
PRD		SDSGB / EN / 0279	J56 / 0091658533 / 0001008286

Result : very slight

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Species : Rabbit
Exposure time : 24 h
Assessment : Not classified
Result : slight

Components:

Tributyl phosphate:

Species : Rabbit
Exposure time : 24 h
Assessment : Not classified
Result : slight irritation

Reaction mass of butyl diphenyl phosphate and dibutyl phenyl phosphate and tributyl phosphate:

Species : Rabbit
Assessment : Not classified
Result : slight

7-Oxabicyclo[4.1.0]heptane-3-carboxylic acid, 2-ethylhexyl ester:

Species : Rabbit
Exposure time : 24 h
Assessment : Not classified
Result : slight irritation

butylated hydroxytoluene:

Species : Rabbit
Result : none

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Product:

Test Type : Human experience
Assessment : Not classified
Method : Human Repeat Insult Patch Test
Result : Does not cause skin sensitization.

SAFETY DATA SHEET

EASTMAN

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758

Skydrol® LD4 Fire Resistant Hydraulic Fluid

Customer PO: POR0113258

Version	Revision Date:	SDS Number:	Date of last issue: 06.08.2020
2.6	05.01.2023	150000093409	Date of first issue: 18.09.2013
PRD		SDSGB / EN / 0279	J56 / 0091658533 / 0001008286

Components:

Tributyl phosphate:

Test Type : Skin Sensitization
Species : Guinea pig
Assessment : Not classified
Result : Does not cause skin sensitization.

Test Type : Skin Sensitization
Species : Humans
Assessment : Not classified
Result : Does not cause skin sensitization.

Reaction mass of butyl diphenyl phosphate and dibutyl phenyl phosphate and tributyl phosphate:

Test Type : Human experience
Species : Humans
Assessment : Not classified
Result : non-sensitizing

7-Oxabicyclo[4.1.0]heptane-3-carboxylic acid, 2-ethylhexyl ester:

Test Type : Skin Sensitization
Species : Guinea pig
Result : May cause sensitization by skin contact.

butylated hydroxytoluene:

Test Type : Skin sensitization
Species : Guinea pig
Result : non-sensitizing

Germ cell mutagenicity

Not classified based on available information.

Product:

Genotoxicity in vitro : Test Type: Salmonella typhimurium assay (Ames test)
Metabolic activation: +/- activation
Result: negative

Test Type: Mutagenicity - Mammalian
Metabolic activation: +/- activation
Method: In vitro Mammalian Chromosome Aberration Test
Result: negative

Components:

Tributyl phosphate:

Genotoxicity in vitro : Test Type: Mutagenicity - Bacterial
Metabolic activation: +/- activation
Method: Bacterial Reverse Mutation Assay

SAFETY DATA SHEET

EASTMAN

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758

Skydrol® LD4 Fire Resistant Hydraulic Fluid

Customer PO: POR0113258

Version	Revision Date:	SDS Number:	Date of last issue: 06.08.2020
2.6	05.01.2023	150000093409	Date of first issue: 18.09.2013
PRD		SDSGB / EN / 0279	J56 / 0091658533 / 0001008286

Result: negative

Test Type: Mutagenicity - Mammalian
Metabolic activation: +/- activation
Method: In vitro Mammalian Chromosome Aberration Test
Result: equivocal

Genotoxicity in vivo : Species: Rat (male and female)
Application Route: oral: gavage
Method: Mammalian Bone Marrow Chromosome Aberration Test
Result: negative

Reaction mass of butyl diphenyl phosphate and dibutyl phenyl phosphate and tributyl phosphate:

Genotoxicity in vitro : Test Type: Salmonella typhimurium assay (Ames test)
Metabolic activation: +/- activation
Method: Bacterial Reverse Mutation Assay
Result: negative

Test Type: Mutagenicity - Mammalian
Metabolic activation: +/- activation
Method: In vitro Mammalian Cell Gene Mutation Test
Result: negative

Metabolic activation: +/- activation
Method: In vitro Mammalian Chromosome Aberration Test
Result: negative

Test Type: Mutagenicity - Mammalian
Metabolic activation: - activation
Method: Genetic Toxicology: DNA Damage and Repair, Un-scheduled DNA Synthesis in Mammalian Cells In Vitro
Result: negative

Genotoxicity in vivo : Species: Rat (male and female)
Application Route: Intraperitoneal injection
Result: negative

7-Oxabicyclo[4.1.0]heptane-3-carboxylic acid, 2-ethylhexyl ester:

Genotoxicity in vitro : Test Type: Salmonella typhimurium assay (Ames test)
Metabolic activation: +/- activation
Method: Bacterial Reverse Mutation Assay
Result: negative

Test Type: Mutagenicity - Mammalian
Metabolic activation: +/- activation
Method: In vitro Mammalian Chromosome Aberration Test
Result: equivocal

Test Type: Mutagenicity - Mammalian

SAFETY DATA SHEET

EASTMAN

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758

Skydrol® LD4 Fire Resistant Hydraulic Fluid

Customer PO: POR0113258

Version	Revision Date:	SDS Number:	Date of last issue: 06.08.2020
2.6	05.01.2023	150000093409	Date of first issue: 18.09.2013
PRD		SDSGB / EN / 0279	J56 / 0091658533 / 0001008286

Metabolic activation: +/- activation
Method: In vitro Mammalian Cell Gene Mutation Test
Result: negative

Genotoxicity in vivo : Species: Rat (male and female)
Application Route: intraperitoneal injection
Method: Mammalian Bone Marrow Chromosome Aberration
Test
Result: equivocal

Carcinogenicity

Suspected of causing cancer.

Product:

Remarks : This information is not available.

Components:

Tributyl phosphate:

Species : Rat, male and female
Application Route : Ingestion
Method : EPA OTS 798.3300
Remarks : Limited evidence of a carcinogenic effect.
May cause cancer.

Reaction mass of butyl diphenyl phosphate and dibutyl phenyl phosphate and tributyl phosphate:

Carcinogenicity - Assessment : Limited evidence of a carcinogenic effect.

Reproductive toxicity

Not classified based on available information.

Product:

Effects on fertility : Remarks: No data available

STOT - single exposure

Not classified based on available information.

Product:

Remarks : No data available

Components:

Tributyl phosphate:

Assessment : Based on available data, the classification criteria are not met.

SAFETY DATA SHEET

EASTMAN

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758

Skydrol® LD4 Fire Resistant Hydraulic Fluid

Customer PO: POR0113258

Version	Revision Date:	SDS Number:	Date of last issue: 06.08.2020
2.6	05.01.2023	150000093409	Date of first issue: 18.09.2013
PRD		SDSGB / EN / 0279	J56 / 0091658533 / 0001008286

Reaction mass of butyl diphenyl phosphate and dibutyl phenyl phosphate and tributyl phosphate:

Assessment : Not classified

STOT - repeated exposure

Not classified based on available information.

Product:

Remarks : No data available

Components:

Tributyl phosphate:

Assessment : Based on available data, the classification criteria are not met.

Reaction mass of butyl diphenyl phosphate and dibutyl phenyl phosphate and tributyl phosphate:

Exposure routes : inhalation (dust/mist/fume)
Target Organs : Respiratory system
Assessment : Not classified

Repeated dose toxicity

Product:

Species : Rat, male and female
NOAEL : 40 mg/m³
Application Route : Inhalation
Exposure time : 28 days
Target Organs : Blood, Respiratory system
Remarks : Irritating to eyes and respiratory system.

Components:

Tributyl phosphate:

Species : Mouse, male and female
: 75 mg/kg
Application Route : in feed
Exposure time : 90 days

Reaction mass of butyl diphenyl phosphate and dibutyl phenyl phosphate and tributyl phosphate:

Species : Rat, male and female
NOAEL : 5 mg/kg
LOAEL : 50 mg/kg
Application Route : in feed
Exposure time : 90 days

Species : Rat, male and female
: 5 mg/m³

SAFETY DATA SHEET

EASTMAN

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758

Skydrol® LD4 Fire Resistant Hydraulic Fluid

Customer PO: POR0113258

Version	Revision Date:	SDS Number:	Date of last issue: 06.08.2020
2.6	05.01.2023	150000093409	Date of first issue: 18.09.2013
PRD		SDSGB / EN / 0279	J56 / 0091658533 / 0001008286

Application Route : Inhalation
Exposure time : 90 days

Species : Rabbit, male and female
NOAEL : 100 mg/kg bw/day
Application Route : Dermal Study
Exposure time : 21 d

Aspiration toxicity

Not classified based on available information.

Product:

Not applicable

Components:

7-Oxabicyclo[4.1.0]heptane-3-carboxylic acid, 2-ethylhexyl ester:

Not applicable

Experience with human exposure

Product:

Inhalation : Remarks: None known.
Skin contact : Remarks: Causes skin irritation.
Eye contact : Remarks: Contact with the eyes may be very painful but does not cause damage.

Further information

Product:

Remarks : None known.

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 5.2 mg/l
Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia magna (Water flea)): 5.8 mg/l
Exposure time: 48 h
Toxicity to algae/aquatic plants : EC50 (Selenastrum capricornutum (green algae)): 8.2 mg/l
Exposure time: 96 h

SAFETY DATA SHEET

EASTMAN

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758

Skydrol® LD4 Fire Resistant Hydraulic Fluid

Customer PO: POR0113258

Version	Revision Date:	SDS Number:	Date of last issue: 06.08.2020
2.6	05.01.2023	150000093409	Date of first issue: 18.09.2013
PRD		SDSGB / EN / 0279	J56 / 0091658533 / 0001008286

Components:

Tributyl phosphate:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 4.2 mg/l
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 1.8 mg/l
aquatic invertebrates Exposure time: 48 h

Toxicity to algae/aquatic : EC50 (Desmodesmus subspicatus (green algae)): 1.1 mg/l
plants Exposure time: 72 h

Toxicity to fish (Chronic tox- : NOEC: 0.82 mg/l
icity) Exposure time: 95 d
Species: Oncorhynchus mykiss (rainbow trout)
1.7 mg/l

Toxicity to daphnia and other : NOEC: 1.3 mg/l
aquatic invertebrates (Chron- Exposure time: 21 d
ic toxicity) Species: Daphnia magna (Water flea)

Reaction mass of butyl diphenyl phosphate and dibutyl phenyl phosphate and tributyl phosphate:

Toxicity to fish : LL50 (Cyprinus carpio (Carp)): 1.8 mg/l
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 1.4 mg/l
aquatic invertebrates Exposure time: 48 h

Toxicity to algae/aquatic : EL50 (Selenastrum capricornutum (green algae)): 9.6 mg/l
plants Exposure time: 72 h
Remarks: EL50 method of the water accommodated fraction
(W.A.F.)
NOELR (Selenastrum capricornutum (green algae)): 3.5 mg/l
Exposure time: 72 h
Remarks: EL50 method of the water accommodated fraction
(W.A.F.)

Toxicity to fish (Chronic tox- : NOEC: > 0.11 mg/l
icity) Exposure time: 60 d
Species: Oncorhynchus mykiss (rainbow trout)

Toxicity to daphnia and other : NOEC: 0.106 mg/l
aquatic invertebrates (Chron- Exposure time: 21 d
ic toxicity) Species: Daphnia magna (Water flea)

Ecotoxicology Assessment

Acute aquatic toxicity : This product has no known ecotoxicological effects.

SAFETY DATA SHEET

EASTMAN

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758

Skydrol® LD4 Fire Resistant Hydraulic Fluid

Customer PO: POR0113258

Version	Revision Date:	SDS Number:	Date of last issue: 06.08.2020
2.6	05.01.2023	150000093409	Date of first issue: 18.09.2013
PRD		SDSGB / EN / 0279	J56 / 0091658533 / 0001008286

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

butylated hydroxytoluene:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 0.57 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 0.48 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (algae)): > 0.24 mg/l
Exposure time: 72 h

NOEC (Pseudokirchneriella subcapitata (algae)): 0.24 mg/l
Exposure time: 72 h

M-Factor (Acute aquatic toxicity) : 1

Toxicity to fish (Chronic toxicity) : NOEC: 0.053 mg/l
Exposure time: 30 d
Species: Oryzias latipes (Orange-red killifish)

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0.069 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)

M-Factor (Chronic aquatic toxicity) : 1

12.2 Persistence and degradability

Product:

Biochemical Oxygen Demand (BOD) : Remarks: not determined

Chemical Oxygen Demand (COD) : Remarks: not determined

Components:

Tributyl phosphate:

Biodegradability : Result: Readily biodegradable.

Reaction mass of butyl diphenyl phosphate and dibutyl phenyl phosphate and tributyl phosphate:

Biodegradability : Method: Ready Biodegradability: Manometric Respirometry Test
Remarks: Readily biodegradable

Method: Ready Biodegradability: Modified MITI Test (I)

SAFETY DATA SHEET

EASTMAN

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758

Skydrol® LD4 Fire Resistant Hydraulic Fluid

Customer PO: POR0113258

Version	Revision Date:	SDS Number:	Date of last issue: 06.08.2020
2.6	05.01.2023	150000093409	Date of first issue: 18.09.2013
PRD		SDSGB / EN / 0279	J56 / 0091658533 / 0001008286

Remarks: Not readily biodegradable.

7-Oxabicyclo[4.1.0]heptane-3-carboxylic acid, 2-ethylhexyl ester:

Biodegradability : Concentration: 100 mg/l
Method: Ready Biodegradability: Modified MITI Test (I)
Remarks: Readily biodegradable

12.3 Bioaccumulative potential

Components:

Tributyl phosphate:

Bioaccumulation : Species: Cyprinus carpio (Carp)
Exposure time: 56 d
Bioconcentration factor (BCF): 20
Method: OECD Test Guideline 305

Exposure time: 38 d
Bioconcentration factor (BCF): 35

Partition coefficient: n-octanol/water : Pow: 10,100

Reaction mass of butyl diphenyl phosphate and dibutyl phenyl phosphate and tributyl phosphate:

Bioaccumulation : Species: Cyprinus carpio (Carp)
Bioconcentration factor (BCF): 35
Method: OECD Test Guideline 305

12.4 Mobility in soil

Components:

Reaction mass of butyl diphenyl phosphate and dibutyl phenyl phosphate and tributyl phosphate:

Distribution among environmental compartments : Koc: 933, log Koc: 2.97
Method: QSAR model

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Product:

SAFETY DATA SHEET

EASTMAN

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758

Skydrol® LD4 Fire Resistant Hydraulic Fluid

Customer PO: POR0113258

Version	Revision Date:	SDS Number:	Date of last issue: 06.08.2020
2.6	05.01.2023	150000093409	Date of first issue: 18.09.2013
PRD		SDSGB / EN / 0279	J56 / 0091658533 / 0001008286

Endocrine disrupting potential : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations.

SECTION 14: Transport information

14.1 UN number

ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.2 UN proper shipping name

ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.4 Packing group

ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA (Cargo) : Not regulated as a dangerous good
IATA (Passenger) : Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

SAFETY DATA SHEET

EASTMAN

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758

Skydrol® LD4 Fire Resistant Hydraulic Fluid

Customer PO: POR0113258

Version	Revision Date:	SDS Number:	Date of last issue: 06.08.2020
2.6	05.01.2023	150000093409	Date of first issue: 18.09.2013
PRD		SDSGB / EN / 0279	J56 / 0091658533 / 0001008286

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17)	:	Conditions of restriction for the following entries should be considered: Number on list 3
UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation	:	Not applicable
The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain)	:	Not applicable
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	:	Not applicable
UK REACH List of substances subject to authorisation (Annex XIV)	:	Not applicable
Control of Major Accident Hazards Regulations 2015 (COMAH)	:	Not applicable
Volatile organic compounds	:	Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Not applicable

The components of this product are reported in the following inventories:

TCSI	:	On the inventory, or in compliance with the inventory
TSCA	:	All substances listed as active on the TSCA inventory
AIIC	:	On the inventory, or in compliance with the inventory
AIIC	:	On the inventory, or in compliance with the inventory
DSL	:	All components of this product are on the Canadian DSL
NZIoC	:	On the inventory, or in compliance with the inventory
ENCS	:	On the inventory, or in compliance with the inventory
IECSC	:	On the inventory, or in compliance with the inventory

SAFETY DATA SHEET

EASTMAN

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758

Skydrol® LD4 Fire Resistant Hydraulic Fluid

Customer PO: POR0113258

Version	Revision Date:	SDS Number:	Date of last issue: 06.08.2020
2.6	05.01.2023	150000093409	Date of first issue: 18.09.2013
PRD		SDSGB / EN / 0279	J56 / 0091658533 / 0001008286

PICCS : On the inventory, or in compliance with the inventory

15.2 Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:
tributyl phosphate

Reaction mass of dibutyl phenyl phosphate, butyl diphenyl phosphate and tributyl phosphate

SECTION 16: Other information

Full text of H-Statements

H302 : Harmful if swallowed.
H315 : Causes skin irritation.
H317 : May cause an allergic skin reaction.
H351 : Suspected of causing cancer.
H400 : Very toxic to aquatic life.
H410 : Very toxic to aquatic life with long lasting effects.
H412 : Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity
Aquatic Acute : Short-term (acute) aquatic hazard
Aquatic Chronic : Long-term (chronic) aquatic hazard
Carc. : Carcinogenicity
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitization
GB EH40 : UK. EH40 WEL - Workplace Exposure Limits
GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of

SAFETY DATA SHEET

EASTMAN

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758

Skydrol® LD4 Fire Resistant Hydraulic Fluid

Customer PO: POR0113258

Version	Revision Date:	SDS Number:	Date of last issue: 06.08.2020
2.6	05.01.2023	150000093409	Date of first issue: 18.09.2013
PRD		SDSGB / EN / 0279	J56 / 0091658533 / 0001008286

Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECl - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information

Other information :

Sources of key data used to compile the Safety Data Sheet : www.EastmanAviationSolutions.com

Classification of the mixture:

Skin Irrit. 2	H315
Carc. 2	H351
Aquatic Chronic 3	H412

Classification procedure:

Calculation method
Calculation method
Based on product data or assessment

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN