

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Issue date: 05/11/2012 Revision date: 13/04/2023 Supersedes version of: 14/10/2022 Version: 3.1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form Trade name

Product code

:	Mixture
:	HYDRAUNYCOIL FH 51
:	FH51-1

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category Use of the substance/mixture Function or use category Industrial use,Professional useMineral oil

: Lubricant

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet NYCO S 66 Avenue des Champs Elysées - BP414 B 75366 Paris Cedex 08 B

75366 Paris Cedex 08 France T +33 (0)1 45 61 50 00 info@nyco-group.com - www.nyco-group.com Supplied by: Sil-Mid Limited Roman Park, Roman Way Coleshill, West Midlands B46 1HG. UK T: 01675 432850 E: info@silmid.com

Emergency Telephone No. +44 (0)1675 432850 (Monday to Friday, 08:00 – 17:30 – GMT)

1.4. Emergency telephone number

Emergency number

: +33 (0)1 45 42 59 59 INRS/ORFILA (France) : 33 1 45 42 59 59

Country	Organisation/Company	Address	Emergency number	Comment
United Kingdom	National Poisons Information Service (Birmingham Centre) City Hospital	Dudley Road B18 7QH	0344 892 0111	Only for healthcare professionals

SECTION 2: Hazards identification	
2.1. Classification of the substance or mixture	
Classification according to Regulation (EC) No. 1272/200 Asp. Tox. 1 Aquatic Chronic 3 Full text of hazard classes, H- and EUH-statements: see sect Adverse physicochemical, human health and environment No additional information available	H304 H412 tion 16
2.2. Label elements	
Labelling according to Regulation (EC) No. 1272/2008 [Cl Hazard pictograms (CLP) :	LP] GHS08
Signal word (CLP): DangContains: Hydr	ger ocarbons, C12-C18, isoalkanes, cyclics, 2-30% aromatics

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Hazard statements (CLP)	: H304 - May be fatal if swallowed and enters airways. H412 - Harmful to aquatic life with long lasting effects.
Precautionary statements (CLP)	 P273 - Avoid release to the environment. P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. P331 - Do NOT induce vomiting. P405 - Store locked up.

2.3. Other hazards

Contains no PBT/vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Hydrocarbons, C12-C18, isoalkanes, cyclics, 2-30% aromatics	EC-No.: 954-225-2 REACH-no: 01-2120920648- 49	50 – 100	Asp. Tox. 1, H304
Hydrocarbons, C13-16	EC-No.: 934-954-2 REACH-no: 01-2119826592- 36	1 - 5	Asp. Tox. 1, H304
2,6-di-tert-butyl-p-cresol substance with national workplace exposure limit(s) (GB)	CAS-No.: 128-37-0 EC-No.: 204-881-4 REACH-no: 01-2119555270- 46	0 - 1	Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Phenol,isopropylated,phosphate	CAS-No.: 68937-41-7 EC-No.: 273-066-3 REACH-no: 01-2119535109- 41	0 – 1	Repr. 2, H361fd STOT RE 2, H373 Aquatic Chronic 1, H410
Methyl methacrylate substance with national workplace exposure limit(s) (GB)	CAS-No.: 80-62-6 EC-No.: 201-297-1 REACH-no: 01-2119452498- 28	0 - 0,1	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Skin Sens. 1B, H317 STOT SE 3, H335
methanol substance with national workplace exposure limit(s) (GB)	CAS-No.: 67-56-1 EC-No.: 200-659-6 EC Index-No.: 603-001-00-X REACH-no: 01-2119433307- 44	0 - 0,01	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 (ATE=100 mg/kg bodyweight) Acute Tox. 3 (Dermal), H311 (ATE=300 mg/kg bodyweight) Acute Tox. 3 (Inhalation), H331 (ATE=0,5 mg/l/4h) STOT SE 1, H370

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
reaction mass of ethylbenzene and xylene substance with national workplace exposure limit(s) (GB)	EC-No.: 905-588-0 REACH-no: 01-2119539452- 40	0 - 0,01	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 (ATE=1100 mg/kg bodyweight) Acute Tox. 4 (Inhalation), H332 (ATE=1,5 mg/l/4h) Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304
cyclohexanone substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit	CAS-No.: 108-94-1 EC-No.: 203-631-1 EC Index-No.: 606-010-00-7 REACH-no: 01-2119453616- 35	0 - 0,001	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 (ATE=1535 mg/kg bodyweight) Acute Tox. 4 (Dermal), H312 (ATE=948 mg/kg bodyweight) Acute Tox. 4 (Inhalation), H332 (ATE=1,5 mg/l/4h) Skin Irrit. 2, H315 Eye Dam. 1, H318

methanol CAS-No.: 67-56-1 (3	Specific concentration limits:		
	Specific concentration limits		
EC Index-No.: 603-001-00-X REACH-no: 01-2119433307- 44	3 ≤C < 10) STOT SE 2, H371 10 ≤C < 100) STOT SE 1, H370		

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

. .

First-aid measures general	: If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Seek medica advice (show the label where possible).
First-aid measures after skin contact	: IF ON SKIN: Wash with plenty of soap and water. Seek medical advice (show the label where possible).
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice (show the label where possible).
First-aid measures after ingestion	: IF SWALLOWED: rinse mouth. Do NOT induce vomiting. Seek medical advice (show the label where possible).
4.2. Most important symptoms and e	ffects, both acute and delayed
Symptoms/effects after inhalation	: At high concentrations, the vapours can be irritating to the respiratory system.
Symptoms/effects after skin contact	: Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after eye contact	: Eye irritation.
Symptoms/effects after ingestion	: Possible irritation of mucous membranes and digestive tract, nausea, vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

SECTION 5: Firefighting measures	
5.1. Extinguishing media	
Suitable extinguishing media Unsuitable extinguishing media	: Water spray. Foam. Dry powder. Carbon dioxide. : Strong water jet.
5.2. Special hazards arising from the subs	tance or mixture
Fire hazard	: On burning: release of harmful/irritant gases/vapours. Carbon oxides (CO, CO2).
5.3. Advice for firefighters	
Precautionary measures fire	: Protective equipment.

SECTION 6: Accidental release measures			
6.1. Personal precautions, protective equipment and emergency procedures			
General measures	: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.		
6.1.1. For non-emergency personnel			
Protective equipment Emergency procedures	See Headings 7 and 8.For a large spillage, contain the spillage by bunding.		
6.1.2. For emergency responders			
Protective equipment Emergency procedures	See Headings 7 and 8.For a large spillage, contain the spillage by bunding.		
6.2. Environmental precautions			
Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.			
6.3. Methods and material for containment and cleaning up			

gel).

Methods for cleaning up

: Soak up with inert absorbent material (for example sand, sawdust, a universal binder, silica

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage		
7.1. Precautions for safe handling		
Additional hazards when processed Precautions for safe handling Hygiene measures	 Stable at ambient temperature and under normal conditions of use. Wear suitable protective clothing. Personal protective equipment. When using do not eat, drink or smoke. Always wash your hands immediately after handling this product, and once again before leaving the workplace. Avoid spilling the product, as this might cause falls. Provide local exhaust or general room ventilation. When using do not eat or drink. Always wash your hands immediately after handling this product, and once again before leaving the workplace. Wash contaminated clothing before reuse. 	
7.2. Conditions for safe storage, including any incompatibilities		
Storage conditions Special rules on packaging	 Store in dry, cool, well-ventilated area. Store in original container. Keep container closed when not in use. 	
7.3. Specific end use(s)		
No additional information available		

13/04/2023 (Revision date) 13/04/2023 (Printing date)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

SECTION 8: Exposure controls/personal protection		
8.1. Control parameters		
8.1.1 National occupational exposure and biological limit values		
2,6-di-tert-butyl-p-cresol (128-37-0)		
United Kingdom - Occupational Exposure Limits		
Local name	2,6-Di-tert-butyl-p-cresol	
WEL TWA (OEL TWA) [1]	10 mg/m³	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	
Methyl methacrylate (80-62-6)		
United Kingdom - Occupational Exposure Limits		
Local name	Methyl methacrylate	
WEL TWA (OEL TWA) [1]	208 mg/m ³	
WEL TWA (OEL TWA) [2]	50 ppm	
WEL STEL (OEL STEL)	416 mg/m ³	
WEL STEL (OEL STEL) [ppm]	100 ppm	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	
reaction mass of ethylbenzene and xylene		
United Kingdom - Occupational Exposure Limits		
Local name	Xylene	
WEL TWA (OEL TWA) [1]	220 mg/m³ o-,m-,p- or mixed isomers	
WEL TWA (OEL TWA) [2]	50 ppm o-,m-,p- or mixed isomers	
WEL STEL (OEL STEL)	441 mg/m³ o-,m-,p- or mixed isomers	
WEL STEL (OEL STEL) [ppm]	100 ppm o-,m-,p- or mixed isomers	
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	
United Kingdom - Biological limit values		
Local name	Xylene, o-, m-, p- or mixed isomers	
BMGV	650 mmol/mol Creatinine Parameter: methyl hippuric acid - Medium: urine - Sampling time: Post shift	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	
methanol (67-56-1)		
United Kingdom - Occupational Exposure Limits		
Local name	Methanol	
WEL TWA (OEL TWA) [1]	266 mg/m ³	
WEL TWA (OEL TWA) [2]	200 ppm	
WEL STEL (OEL STEL)	333 mg/m ³	
WEL STEL (OEL STEL) [ppm]	250 ppm	

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

methanol (67-56-1)		
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	
cyclohexanone (108-94-1)		
EU - Indicative Occupational Exposure Limit (IOEL)		
IOEL TWA	40,8 mg/m ³	
IOEL TWA [ppm]	10 ppm	
IOEL STEL	81,6 mg/m³	
IOEL STEL [ppm]	20 ppm	
United Kingdom - Occupational Exposure Limits		
Local name	Cyclohexanone	
WEL TWA (OEL TWA) [1]	41 mg/m ³	
WEL TWA (OEL TWA) [2]	10 ppm	
WEL STEL (OEL STEL)	82 mg/m ³	
WEL STEL (OEL STEL) [ppm]	20 ppm	
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	
United Kingdom - Biological limit values		
Local name	Cyclohexanone	
BMGV	2 mmol/mol Creatinine Parameter: cyclohexanol - Medium: urine - Sampling time: Post shift	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	
Oil mist		
EU - Indicative Occupational Exposure Limit (IOEL)		
IOEL TWA	5 mg/m³ 8h	
IOEL STEL	10 mg/m³ 15min	

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

2,6-di-tert-butyl-p-cresol (128-37-0)	
DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	0,5 mg/kg bodyweight/day
_ong-term - systemic effects, inhalation 1,76 mg/m³	
DNEL/DMEL (General population)	
Long-term - systemic effects,oral	0,25 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	0,435 mg/m³

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

2,6-di-tert-butyl-p-cresol (128-37-0)	2,6-di-tert-butyl-p-cresol (128-37-0)		
Long-term - systemic effects, dermal	0,25 mg/kg bodyweight/day		
PNEC (Water)			
PNEC aqua (freshwater)	0,199 µg/l		
PNEC aqua (marine water)	0,0199 µg/l		
PNEC aqua (intermittent, freshwater)	1,99 µg/l		
PNEC (Sediment)			
PNEC sediment (freshwater)	0,45819 mg/kg dwt		
PNEC sediment (marine water)	0,04582 mg/kg dwt		
PNEC (Soil)			
PNEC soil	0,0539 mg/kg dwt		
PNEC (Oral)			
PNEC oral (secondary poisoning)	16,67 mg/kg food		
PNEC (STP)	·		
PNEC sewage treatment plant	0,017 mg/l		
Phenol, isopropylated, phosphate (68937-41-7)			
DNEL/DMEL (Workers)			
Acute - systemic effects, dermal	2000 mg/kg bodyweight/day		
Acute - systemic effects, inhalation	700 mg/m ³		
Acute - local effects, dermal	16 mg/cm ²		
Long-term - systemic effects, dermal	0,417 mg/kg bodyweight/day		
Long-term - systemic effects, inhalation	0,145 mg/m³		
DNEL/DMEL (General population)			
Acute - systemic effects, dermal	100 mg/kg bodyweight		
Acute - systemic effects, inhalation	350 mg/m³		
Acute - local effects, dermal	8 mg/cm ²		
Long-term - systemic effects,oral	0,04 mg/kg bodyweight/day		
Long-term - systemic effects, inhalation	0,07 mg/m ³		
Long-term - systemic effects, dermal	0,208 mg/kg bodyweight/day		
PNEC (Water)			
PNEC aqua (freshwater)	0,00031 mg/l		
PNEC aqua (marine water)	0,000031 mg/l		
PNEC (Sediment)			
PNEC sediment (freshwater)	0,185 mg/kg dwt		
PNEC sediment (marine water)	0,0185 mg/kg dwt		
PNEC (Soil)			
PNEC soil	2,5 mg/kg dwt		
PNEC (STP)			
PNEC sewage treatment plant	100 mg/l		

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

No additional information available

8.2.2. Personal protection equipment

Personal protective equipment:

Gloves. Safety glasses. Protective clothing.

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection: Safety glasses with side shields

8.2.2.2. Skin protection

Skin and body protection: Wear suitable protective clothing

Hand protection: Chemical resistant gloves (according to European standard NF ISO 374-1 or equivalent)

8.2.2.3. Respiratory protection

Respiratory protection:

No personal breathing protective equipment is normally required

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Do not flush into surface water or sewer system.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: red.
Odour	: Not available
Odour threshold	: Not available
Melting point	: -69 °C
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Not available
Explosive limits	: Not available
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: 91 °C
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
рН	: Not applicable
Viscosity, kinematic	: 14,12 mm²/s @40°C
Solubility	: insoluble in water.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: 0,87 kg/l @20°C
Relative density	: Not available
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity		
10.1. Reactivity		
Stable at ambient temperature and under normal conditions of use.		
10.2. Chemical stability		
No additional information available		
10.3. Possibility of hazardous reactions		
No additional information available		
10.4. Conditions to avoid		
elevated temperature.		
10.5. Incompatible materials		
Strong oxidizing agents.		

10.6. Hazardous decomposition products

No hazardous decomposition products known at room temperature.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008		
Acute toxicity (dermal)	Not classified Not classified Not classified	
Hydrocarbons, C12-C18, isoalkanes, cyclics, 2-30% aromatics		
LD50 oral rat	> 4150 mg/kg (Results obtained on a similar product)	
LD50 dermal rabbit	> 1700 mg/l (Results obtained on a similar product)	
LC50 Inhalation - Rat (Dust/Mist)	> 5,28 mg/l/4h (Results obtained on a similar product)	
Hydrocarbons, C13-16		
LD50 oral rat	> 5000 mg/kg bodyweight OECD 401	
LD50 dermal rabbit	> 3160 mg/kg OECD 402	
LC50 Inhalation - Rat (Vapours)	> 5,26 mg/l/4h OECD 403	

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

LD50 oral rat > 2930 mg/kg DECD 401 LD50 demail rat > 2000 mg/kg bodyweight OECD 402 Phenol.lsopropylated.phosphate (68937-41-7) > LD50 oral rat > 5000 mg/kg LD50 demail ratbit > 10000 mg/kg LD50 demail rabbit > 200 mg/l reaction mass of ethylbenzene and xylene > LD50 oral rat 3523 mg/kg bw/day methanol (67-56-1) > LD50 demail rabbit 15800 mg/kg LD50 demail rabbit 1620 mg/kg LD50 demail rabbit > 794 - <3100 mg/kg LD50 demail rabbit > 794 - <3100 mg/kg LD50 demail rabbit > Not classified Skin corroson/inflation : Not classified Gern cell multigenerity : Not classified Skin corroson/inflation : Not classified Scin seys damagelintration : Not classified Carcinogenicity : Not classified Scin seys damagelintratino : Not classif	2,6-di-tert-butyl-p-cresol (128-37-0)	2,6-di-tert-butyl-p-cresol (128-37-0)		
Phenol,Isopropylated,phosphate (68937-41-7) LD50 oral rat > 5000 mg/kg LD50 demal rabbit > 10000 mg/kg LD50 names of ethylbenzone and xylone Image: Comparison of thylbenzone and xylone LD50 oral rat 3523 mg/kg bw/day methanol (67-56-1) Image: Comparison of thylbenzone and xylone LD50 oral rat > 2528 mg/kg OECD 401 LD50 oral rat > 2528 mg/kg OECD 401 LD50 oral rat > 2528 mg/kg OECD 401 LD50 oral rat 1620 mg/kg LD50 deminal rabbit > 784 –< 3160 mg/kg	LD50 oral rat	> 2930 mg/kg OECD 401		
L050 oral rat > 5000 mg/kg L050 dermal rabbit > 10000 mg/kg LC50 Inhalation - Rat > 200 mg/l reaction mass of ethylbenzene and xylene ID50 oral rat L050 oral rat 3523 mg/kg bw/day methanol (67-56-1) - L050 oral rat > 2528 mg/kg 0ECD 401 L050 oral rat > 2528 mg/kg 0ECD 401 L050 oral rat > 2528 mg/kg 0ECD 401 L050 oral rat 1620 mg/kg L050 dermal rabbit > 794 - < 3160 mg/kg	LD50 dermal rat	> 2000 mg/kg bodyweight OECD 402		
LD50 dermal rabbit > 10000 mg/kg LC50 Inhalation - Rat > 200 mg/l reaction mass of othylbonzone and xylone JS23 mg/kg bw/day methanol (67-56-1) - LD50 oral rat > 2528 mg/kg DECD 401 LD50 oral rat 1620 mg/kg LD50 oral rat 1620 mg/kg LD50 oral rat 1620 mg/kg LD50 dermal rabbit > 744 - < 3160 mg/kg	Phenol,isopropylated,phosphate (68937-41-7)			
LC50 Inhalation - Rat > 200 mg/l reaction mass of ethylbenzene and xylene LD50 oral rat 3523 mg/kg bw/day methanol (67-56-1) LD50 deral rat > 2528 mg/kg OECD 401 LD50 deral rabil 15800 mg/kg LC50 Inhalation - Rat (Vapours) 128.2 mg/l/4h cyclohexanone (108-94-1) LD50 deral rabil > 754 - < 3160 mg/kg	LD50 oral rat	> 5000 mg/kg		
reaction mass of othylbenzone and xylene LD50 oral rat 3523 mg/kg bw/day methanol (67-56-1) LD50 oral rat > 2528 mg/kg OECD 401 LD50 dermal rabbit 15800 mg/kg LC50 halation - Rat (Vapours) 128.2 mg/k/h cyclohexanone (108-94-1) LD50 oral rat 1620 mg/kg LD50 armal rabbit > 794 - < 3180 mg/kg	LD50 dermal rabbit	> 10000 mg/kg		
LD50 oral rat 3523 mg/kg bw/day methanol (67-56-1) LD50 oral rat > 2528 mg/kg OECD 401 LD50 dermal rabbit 15800 mg/kg LC50 inhalation - Rat (Vapours) 128,2 mg/k4h cyclohexanone (108-94-1) LD50 dermal rabbit > 794 - < 3160 mg/kg	LC50 Inhalation - Rat	> 200 mg/l		
methanol (67-56-1) LD50 oral rat > 2528 mg/kg OECD 401 LD50 dermal rabbit 15800 mg/kg LC50 Inhalation - Rat (Vapours) 128.2 mg/k4h cyclohexanone (108-94-1) 1520 mg/kg LD50 oral rat 1620 mg/kg LD50 dermal rabbit > 754 - < 3160 mg/kg	reaction mass of ethylbenzene and xylene			
LD50 oral rat > 2528 mg/kg OECD 401 LD50 dermal rabbit 15800 mg/kg LC50 Inhalation - Rat (Vapours) 128.2 mg/l/4h cyclohexanone (108-94-1) LD50 dermal rabbit > 794 – < 3160 mg/kg	LD50 oral rat	3523 mg/kg bw/day		
LD50 dermal rabbit 15800 mg/kg LC50 Inhilation - Rat (Vapours) 128,2 mg/l/4h cyclohexanone (108-94-1) 128,2 mg/l/4h LD50 oral rat 1620 mg/kg LD50 dermal rabbit > 794 - < 3160 mg/kg	methanol (67-56-1)			
LC50 Inhalation - Rat (Vapours) 128.2 mg/l/4h cyclohexanone (108-94-1) 1520 mg/kg LD50 oral rat 1620 mg/kg LC50 Inhalation - Rat 8000 mg/l/4h Skin corrosion/irritation : Not classified pH: Not applicable pH: Not applicable Serious eye damage/irritation : Not classified gem cell mutagenicity : Not classified Gem cell mutagenicity : Not classified Carcinogenicity : Not classified Carcinogenicity : Not classified StOT-single exposure : Not classified StOT-single exposure May cause respiratory irritation. reaction mass of ethylbenzene and xylene StOT-single exposure STOT-single exposure Causes damage to organs. STOT-repeated exposure : Not classified Phenol, isopropylated,phosphate (68937-41-7) StOT-repeated exposure STOT-repeated exposure May cause damage to organs. STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure. reaction mass of ethylbenzene and xylene Stora set forgans through prolonged or repeated exposure. STOT-repeated exposure May cause damage to organs through	LD50 oral rat	> 2528 mg/kg OECD 401		
cyclohexanone (108-94-1) LD50 oral rat 1620 mg/kg LD50 dermal rabbit > 794 – < 3160 mg/kg	LD50 dermal rabbit	15800 mg/kg		
LD50 oral rat 1620 mg/kg LD50 dermal rabbit > 794 - < 3160 mg/kg	LC50 Inhalation - Rat (Vapours)	128,2 mg/l/4h		
LD50 dermal rabbit > 794 - < 3160 mg/kg	cyclohexanone (108-94-1)			
LC50 Inhalation - Rat 8000 mg/l/4h Skin corrosion/irritation in Not classified pH: Not applicable Serious eye damage/irritation in Not classified pH: Not applicable Respiratory or skin sensitisation in Not classified Germ cell mutagenicity in Not classified Carcinogenicity in Not classified Reproductive toxicity in Not classified STOT-single exposure in Not classified STOT-single exposure May cause respiratory irritation. reaction mass of ethylbenzene and xylene May cause respiratory irritation. STOT-single exposure in Not classified STOT-single exposure Causes damage to organs. STOT-single exposure in Not classified Phenol, isopropylated, phosphate (68937-41-7) STOT-repeated exposure STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure. reaction mass of ethylbenzene and xylene Stor cause damage to organs through prolonged or repeated exposure. STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure. reaction mass of ethylbenzene and xylene Stor cause damage to organs through prolonged or repeated exposure. STOT-repeated exposure May	LD50 oral rat	1620 mg/kg		
Skin corrosion/irritation : Not classified pH: Not applicable Serious eye damage/irritation : Not classified pH: Not applicable Respiratory or skin sensitisation : Not classified Gern cell mutagenicity : Not classified Garcinogenicity : Not classified Reproductive toxicity : Not classified STOT-single exposure : Not classified STOT-single exposure May cause respiratory irritation. reaction mass of ethylbenzene and xylene Stot classified STOT-single exposure : Not classified STOT-single exposure May cause respiratory irritation. methanol (67-56-1) Stot classified STOT-repeated exposure : Not classified Phenol,isopropylated,phosphate (68937-41-7) Stot classified STOT-repeated exposure May cause damage to organs. STOT-repeated exposure May cause damage to organs. STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure. reaction mass of ethylbenzene and xylene Stot-repeated exposure. STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure.	LD50 dermal rabbit	> 794 – < 3160 mg/kg		
pH: Not applicable Serious eye damage/irritation : Not classified Respiratory or skin sensitisation : Not classified Gern cell mutagenicity : Not classified Garn cogenicity : Not classified Reproductive toxicity : Not classified Reproductive toxicity : Not classified STOT-single exposure : Not classified STOT-single exposure May cause respiratory irritation. reaction mass of ethylbenzene and xylene StoTo-single exposure STOT-single exposure Causes damage to organs. STOT-sepeated exposure : Not classified Phenol,isopropylated,phosphate (68937-41-7) StoTo-repeated exposure STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure. reaction mass of ethylbenzene and xylene StoTo-repeated exposure. StoT-repeated exposure May cause damage to organs through prolonged or repeated exposure. reaction mass of ethylbenzene and xylene StoT-repeated exposure. StoT-repeated exposure May cause damage to organs through prolonged or repeated exposure. reaction mass of ethylbenzene and xylene StoT-repeated exposure. StoT-repeated exposure May cause damage	LC50 Inhalation - Rat	8000 mg/l/4h		
Serious eye damage/irritation : Not classified pH: Not applicable Respiratory or skin sensitisation : Not classified Germ cell mutagenicity : Not classified Carcinogenicity : Not classified Reproductive toxicity : Not classified STOT-single exposure : Not classified Methyl methacrylate (80-62-6) STOT-single exposure STOT-single exposure May cause respiratory irritation. reaction mass of ethylbenzene and xylene STOT-single exposure STOT-single exposure May cause respiratory irritation. methanol (67-56-1) STOT-single exposure STOT-single exposure Causes damage to organs. STOT-repeated exposure : Not classified Phenol,isopropylated,phosphate (68937-41-7) STOT-repeated exposure STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure. reaction mass of ethylbenzene and xylene STOT-repeated exposure STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure. reaction mass of ethylbenzene and xylene STOT-repeated exposure STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure. <td< td=""><td>Skin corrosion/irritation :</td><td></td></td<>	Skin corrosion/irritation :			
Respiratory or skin sensitisation : Not classified Gern cell mutagenicity : Not classified Carcinogenicity : Not classified Reproductive toxicity : Not classified STOT-single exposure May cause respiratory irritation. reaction mass of ethylbenzene and xylene STOT-single exposure STOT-single exposure May cause respiratory irritation. methanol (67-56-1) Causes damage to organs. STOT-repeated exposure : Not classified Phenol,isopropylated,phosphate (68937-41-7) STOT-repeated exposure STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure. reaction mass of ethylbenzene and xylene STOT-repeated exposure STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure. STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure. STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure. STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure.	Serious eye damage/irritation :			
Gern cell mutagenicity : Not classified Carcinogenicity : Not classified Reproductive toxicity : Not classified STOT-single exposure : Not classified Methyl methacrylate (80-62-6) STOT-single exposure May cause respiratory irritation. reaction mass of ethylbenzene and xylene May cause respiratory irritation. STOT-single exposure May cause respiratory irritation. methanol (67-56-1) STOT-single exposure Causes damage to organs. STOT-single exposure : Not classified Phenol,isopropylated,phosphate (68937-41-7) STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure. reaction mass of ethylbenzene and xylene May cause damage to organs through prolonged or repeated exposure. reaction mass of ethylbenzene and xylene May cause damage to organs through prolonged or repeated exposure. STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure. reaction mass of ethylbenzene and xylene StOT-repeated exposure STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure. Aspiration hazard : May be fatal if swallowed and enters airways. <td></td> <td></td>				
Carcinogenicity : Not classified Reproductive toxicity : Not classified STOT-single exposure : Not classified Methyl methacrylate (80-62-6) STOT-single exposure STOT-single exposure May cause respiratory irritation. reaction mass of ethylbenzene and xylene STOT-single exposure STOT-single exposure May cause respiratory irritation. methanol (67-56-1) STOT-single exposure STOT-single exposure Causes damage to organs. STOT-repeated exposure : Not classified Phenol,isopropylated,phosphate (68937-41-7) STOT-repeated exposure STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure. reaction mass of ethylbenzene and xylene STOT-repeated exposure STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure. reaction mass of ethylbenzene and xylene STOT-repeated exposure STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure. Aspiration hazard : May be fatal if swallowed and enters airways. HYDRAUNYCOIL FH 51 Image: Stot Stot Stot Stot Stot Stot Stot Sto	1 3			
Reproductive toxicity : Not classified STOT-single exposure : Not classified Methyl methacrylate (80-62-6) : STOT-single exposure May cause respiratory irritation. reaction mass of ethylbenzene and xylene : STOT-single exposure May cause respiratory irritation. reaction mass of ethylbenzene and xylene : STOT-single exposure May cause respiratory irritation. methanol (67-56-1) : STOT-repeated exposure : Causes damage to organs. STOT-repeated exposure : Not classified Phenol,isopropylated,phosphate (68937-41-7) : STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure. reaction mass of ethylbenzene and xylene : May cause damage to organs through prolonged or repeated exposure. STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure. reaction mass of ethylbenzene and xylene : May cause damage to organs through prolonged or repeated exposure. Aspiration hazard : May be fatal if swallowed and enters airways. HYDRAUNYCOLL FH 51 : May be fatal if swallowed and enters airways.				
STOT-single exposure Not classified Methyl methacrylate (80-62-6) STOT-single exposure STOT-single exposure May cause respiratory irritation. reaction mass of ethylbenzene and xylene STOT-single exposure STOT-single exposure May cause respiratory irritation. methanol (67-56-1) STOT-single exposure STOT-repeated exposure Causes damage to organs. STOT-repeated exposure Not classified Phenol,isopropylated,phosphate (68937-41-7) STOT-repeated exposure STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure. reaction mass of ethylbenzene and xylene STOT-repeated exposure STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure. reaction mass of ethylbenzene and xylene STOT-repeated exposure STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure. Aspiration hazard May be fatal if swallowed and enters airways. HYDRAUNYCOIL FH 51 Image: Stot Stot Stot Stot Stot Stot Stot Sto				
Methyl methacrylate (80-62-6) STOT-single exposure May cause respiratory irritation. reaction mass of ethylbenzene and xylene STOT-single exposure STOT-single exposure May cause respiratory irritation. methanol (67-56-1) STOT-single exposure STOT-repeated exposure Causes damage to organs. STOT-repeated exposure Not classified Phenol,isopropylated,phosphate (68937-41-7) STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure. reaction mass of ethylbenzene and xylene STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure. reaction mass of ethylbenzene and xylene STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure. Aspiration hazard : May be fatal if swallowed and enters airways. HYDRAUNYCOIL FH 51 HYDRAUNYCOIL FH 51	-			
STOT-single exposure May cause respiratory irritation. reaction mass of ethylbenzene and xylene STOT-single exposure May cause respiratory irritation. methanol (67-56-1) STOT-single exposure Causes damage to organs. STOT-repeated exposure : Not classified Phenol,isopropylated,phosphate (68937-41-7) STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure. reaction mass of ethylbenzene and xylene STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure. reaction mass of ethylbenzene and xylene STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure. Aspiration hazard : May be fatal if swallowed and enters airways. HYDRAUNYCOIL FH 51				
reaction mass of ethylbenzene and xylene STOT-single exposure May cause respiratory irritation. methanol (67-56-1) STOT-single exposure STOT-single exposure Causes damage to organs. STOT-repeated exposure Not classified Phenol,isopropylated,phosphate (68937-41-7) STOT-repeated exposure STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure. reaction mass of ethylbenzene and xylene STOT-repeated exposure STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure. Aspiration hazard : May be fatal if swallowed and enters airways. HYDRAUNYCOIL FH 51 Image: Store in the stor		· · · · · · · · · · · · · · · · · · ·		
STOT-single exposure May cause respiratory irritation. methanol (67-56-1) STOT-single exposure STOT-single exposure Causes damage to organs. STOT-repeated exposure : Not classified Phenol,isopropylated,phosphate (68937-41-7) STOT-repeated exposure STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure. reaction mass of ethylbenzene and xylene STOT-repeated exposure STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure. Aspiration hazard : May be fatal if swallowed and enters airways. HYDRAUNYCOIL FH 51 Image: Store in the		May cause respiratory irritation.		
methanol (67-56-1) STOT-single exposure Causes damage to organs. STOT-repeated exposure Not classified Phenol,isopropylated,phosphate (68937-41-7) STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure. reaction mass of ethylbenzene and xylene STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure. stoT-repeated exposure May cause damage to organs through prolonged or repeated exposure. Aspiration hazard May be fatal if swallowed and enters airways. HYDRAUNYCOIL FH 51 HYDRAUNYCOIL FH 51				
STOT-single exposure Causes damage to organs. STOT-repeated exposure : Not classified Phenol,isopropylated,phosphate (68937-41-7) STOT-repeated exposure STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure. reaction mass of ethylbenzene and xylene STOT-repeated exposure STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure. STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure. Aspiration hazard : May be fatal if swallowed and enters airways. HYDRAUNYCOIL FH 51 Image to provide the synthematic structure in the synthe synthe synthematic structure in the synthe synthema	STOT-single exposure	May cause respiratory irritation.		
STOT-repeated exposure : Not classified Phenol,isopropylated,phosphate (68937-41-7) STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure. reaction mass of ethylbenzene and xylene STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure. STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure. Aspiration hazard : May be fatal if swallowed and enters airways. HYDRAUNYCOIL FH 51	methanol (67-56-1)			
Phenol,isopropylated,phosphate (68937-41-7) STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure. reaction mass of ethylbenzene and xylene STOT-repeated exposure STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure. Aspiration hazard : May be fatal if swallowed and enters airways. HYDRAUNYCOIL FH 51 Image: State organs through prolonged or repeated exposure.		Causes damage to organs.		
STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure. reaction mass of ethylbenzene and xylene STOT-repeated exposure STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure. Aspiration hazard : May be fatal if swallowed and enters airways. HYDRAUNYCOIL FH 51 Image: Store in the				
reaction mass of ethylbenzene and xylene STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure. Aspiration hazard : May be fatal if swallowed and enters airways. HYDRAUNYCOIL FH 51	Phenol,isopropylated,phosphate (68937-41-7)			
STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure. Aspiration hazard : May be fatal if swallowed and enters airways. HYDRAUNYCOIL FH 51	STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.		
Aspiration hazard : May be fatal if swallowed and enters airways. HYDRAUNYCOIL FH 51	reaction mass of ethylbenzene and xylene			
HYDRAUNYCOIL FH 51	STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.		
	Aspiration hazard :	May be fatal if swallowed and enters airways.		
Viscosity, kinematic 14,12 mm²/s @40°C	HYDRAUNYCOIL FH 51			
	Viscosity, kinematic	14,12 mm²/s @40°C		

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Hydrocarbons, C12-C18, isoalkanes, cyclics, 2-30% aromatics		
Viscosity, kinematic	3 mm²/s @40°C	
Hydrocarbons, C13-16		
Viscosity, kinematic	3 – 4 mm²/s @20°C	
11.2. Information on other hazards		

No additional information available

SECTION 12: Ecological information

12.1. Toxicity		
Hazardous to the aquatic environment, short–term : Not classified (acute) Hazardous to the aquatic environment, long–term : Harmful to aquatic life with long lasting effects. (chronic)		
Hydrocarbons, C12-C18, isoalkanes, cyclics, 2	2-30% aromatics	
LC50 - Fish [1]	> 1000 mg/l 96h	
EC50 - Crustacea [1]	> 1000 mg/l 48h	
Hydrocarbons, C13-16		
LC50 - Fish [1]	> 1028 mg/l 96h:Scophthalmus maximus (OCDE203)	
EC50 - Crustacea [1]	> 3193 mg/l 48h:Acartia tonsa (ISO 14669)	
EC50 72h - Algae [1]	> 10000 mg/l 72h:Skeletonema costatum (ISO 10253)	
NOEC chronic fish	> 1000 mg/l 28d:Oncorhynchus mykiss (QSAR)	
NOEC chronic crustacea	> 1000 mg/l 28d:Daphnia magna (QSAR)	
2,6-di-tert-butyl-p-cresol (128-37-0)		
LC50 - Fish [1]	> 0,57 mg/l 96h:Danio rerio (EC n° 440/2008, annexe, C.1)	
EC50 - Crustacea [1]	0,48 mg/l 48h:Daphnia magna (OECD 202)	
EC50 72h - Algae [1]	> 0,4 mg/l 72h:Desmodesmus subspicatus (EC n° 440/2008, annexe, C.3)	
NOEC chronic fish	0,053 mg/l 42d:Oryzias latipes (OECD 210)	
NOEC chronic crustacea	0,023 mg/l 21d:Daphnia magna (OCDE 202)	
Phenol,isopropylated,phosphate (68937-41-7)		
LC50 - Fish [1]	10,8 mg/l 96h:Pimephales promelas	
LC50 - Fish [2]	1,6 mg/l 96h:Oncorhynchus mykiss	
EC50 - Crustacea [1]	2,44 mg/l 48h:Daphnia magna	
NOEC chronic fish	0,0031 mg/l 33d:Pimephales promelas (OECD 210)	
NOEC chronic crustacea	0,041 mg/l 21d:Daphnia magna (OECD 211)	
reaction mass of ethylbenzene and xylene		
LC50 - Fish [1]	2,6 mg/l 96h	
EC50 - Crustacea [1]	> 3,4 mg/l Test organisms (species): Ceriodaphnia dubia	
EC50 - Crustacea [2]	1 mg/l Daphnia magma	

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

reaction mass of ethylbenzene and xylene		
NOEC chronic fish	> 1,3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d'	
NOEC chronic crustacea	0,96 mg/l 7d; Daphnia magma	
methanol (67-56-1)		
LC50 - Fish [1]	15400 mg/l 96h:Lepomis macrochirus (EPA-660/3-75-009)	
EC50 - Crustacea [1]	> 10000 ml/l 48h:Daphnia magna (DIN 38412)	
ErC50 algae	22000 mg/l 96h:Pseudokirchneriella (OECD 201)	
cyclohexanone (108-94-1)		
LC50 - Fish [1]	527 mg/l 96h:Pimephales promelas	
EC50 - Crustacea [1]	> 100 mg/l Daphnia	
EC50 72h - Algae [1]	> 100 mg/l Scenedesmus subspicatus	
NOEC chronic algae	≥ 100 mg/l Scenedesmus subspicatus	

12.2. Persistence and degradability

2,6-di-tert-butyl-p-cresol (128-37-0)		
Persistence and degradability	Not readily biodegradable.	
Biodegradation	4,5 % 28d; OECD301 C	
Phenol,isopropylated,phosphate (68937-41-7)		
Biodegradation	17,9 % 28d	
methanol (67-56-1)		
Persistence and degradability	Readily biodegradable.	
Biodegradation	76 % 5d	

12.3. Bioaccumulative potential

Hydrocarbons, C12-C18, isoalkanes, cyclics, 2-30% aromatics	
Bioaccumulative potential	Potentially bioaccumulable.
2,6-di-tert-butyl-p-cresol (128-37-0)	
Bioconcentration factor (BCF REACH)	> 2000
Partition coefficient n-octanol/water (Log Pow)	5,1
reaction mass of ethylbenzene and xylene	
Partition coefficient n-octanol/water (Log Kow) < 3	
methanol (67-56-1)	
Partition coefficient n-octanol/water (Log Pow) -0,77	
12.4. Mobility in soil	
2,6-di-tert-butyl-p-cresol (128-37-0)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	3,9 - 4,2

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

12.5. Results of PBT and vPvB assessment	
No additional information available	
12.6. Endocrine disrupting properties	
No additional information available	
12.7. Other adverse effects	
No additional information available	

SECTION 13:	Disposal	considera	itions
-------------	----------	-----------	--------

13.1. Waste treatment methods

Waste treatment methods

: Collect all waste in suitable and labelled containers and dispose according to local legislation.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID				
ADR	IMDG	ΙΑΤΑ	ADN	RID
14.1. UN number or ID number				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.2. UN proper shipping name				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.4. Packing group				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.5. Environmental hazards				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available				

14.6. Special precautions for user

Overland transport Not regulated

Notregulated

Transport by sea Not regulated

Air transport Not regulated

Inland waterway transport Not regulated

Rail transport Not regulated

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Seveso Directive (Disaster Risk Reduction)

Seveso III Part II (Named dangerous substances)	Qualifying quantity (tonnes)	
	Lower-tier	Upper-tier
22. Methanol	500	5000

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Full text of H- and EUH-statements:	
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 3 (Inhalation)	Acute toxicity (inhal.), Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Full text of H- and EUH	I-statements:
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.
H370	Causes damage to organs.
H371	May cause damage to organs.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1B	Skin sensitisation, category 1B
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 1	Specific target organ toxicity – single exposure, Category 1
STOT SE 2	Specific target organ toxicity – Single exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.