



### PRODUCT DESCRIPTION

<b>Backing:</b>	Interior Grade Aromatic Polyurethane
<b>Adhesive:</b>	Urethane Based
<b>Liner:</b>	92 lb Coated Kraft Paper
<b>Color:</b>	Transparent

### APPLICATIONS

- Floor joint sealing on aircraft decking in all wet areas including:
  - Entryways
  - Galleys
  - Lavatories
  - Other areas susceptible to moisture
- Surface Protection
- Sound Dampening

### FEATURES AND BENEFITS

- Tough & Durable.
- Moisture Resistant.
- Flame retardant- meet FAR25.853(a).
- Helps prevent corrosion on floor structures.
- Can be used directly over wet sealant.
- Easy to apply.
- Allows wide-width usage; can be die cut.
- Meets BMS 8-346C, Airbus 10-05-004.

### PHYSICAL PROPERTIES

	<b>Standard UOM</b>	<b>Metric UOM</b>	<b>Test Method</b>
Total Thickness (w/o liner)	9.0 mils	228 microns	PSTC 133
Substrate Thickness	7.0 mils	178 microns	PSTC 133
Adhesion Steel	40 oz/in	436 N/m	ASTM D3330
Tensile Strength	60 lb/in	10508 N/m	ASTM D3759
Elongation	600 %		
Taber Abrasion/Wear Index	0.57		ASTM D4060
Application Temperature	50°F to 120°F	10°C to 49°C	
Operating Temperature	-65°F to 300°F	-54°C to 149°C	

Shelf Life @ 25°C (77°F): 24 months

Recommended Storage Conditions: 40-60% Humidity, 60°F - 80°F

The information presented herein was prepared at BERRY PLASTICS CORPORATION (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To Berry Plastics' knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY PLASTICS assumes any legal responsibility.