# LPS

### SAFETY DATA SHEET

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation

A-151 (Aerosol)

of the mixture

Registration number

Synonyms None.

Part Number 04320, M04320 Issue date 27-September-2015

Version number 02

Revision date 05-October-2016 Supersedes date 27-September-2015

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses A solvent degreaser designed for removing heavy residues from metal and other hard surfaces

where reduced flammability, toxicity and environmental impact are concerns.

Uses advised against None known.

#### 1.3. Details of the supplier of the safety data sheet

Supplier Alsco Ltd

Company name Unit 13 Hillmead Industrial Estate

Address Marshall Road

Swindon, Wiltshire

United Kingdom SN5 5FZ

Telephone +44 1793 733 900 In Case of Emergency +001 703-527-3887

Manufacturer

Company name ITW Pro Brands

Address 4647 Hugh Howell Rd., Tucker, GA 30084 (U.S.A.)

Website http://www.lpslabs.com
e-mail lpssds@itwprobrands.com

#### **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

#### Classification according to Directive 67/548/EEC or 1999/45/EC as amended

Classification F+;R12, Xn;R65, Xi;R38, R67

The full text for all R-phrases is displayed in section 16.

#### Classification according to Regulation (EC) No 1272/2008 as amended

**Physical hazards** 

Aerosols Category 1 H222 - Extremely flammable

aerosol.

H229 - Pressurized container: May

burst if heated.

**Health hazards** 

exposure

Skin corrosion/irritation Category 2 H315 - Causes skin irritation.

Specific target organ toxicity - single Category 3 narcotic effects H336 - May cause drowsiness or

dizziness.

Aspiration hazard Category 1 H304 - May be fatal if swallowed

and enters airways.

**Hazard summary** 

Physical hazards Extremely flammable.

04320, M04320 Version #: 02 Revision date: 05-October-2016 Issue date: 27-September-2015

Health hazards Irritating to skin. Harmful: may cause lung damage if swallowed. Vapours may cause drowsiness

and dizziness. Occupational exposure to the substance or mixture may cause adverse health

effects.

**Environmental hazards** Not classified for hazards to the environment.

Specific hazards Extremely flammable. Harmful: may cause lung damage if swallowed. Irritating to skin. Do not

breathe dust/fume/gas/mist/vapors/spray.

Main symptoms Aspiration may cause pulmonary oedema and pneumonitis. May cause drowsiness and dizziness.

Headache. Nausea, vomiting. Skin irritation. May cause redness and pain.

#### 2.2. Label elements

#### Label according to Regulation (EC) No. 1272/2008 as amended

Contains: Distillates Petroleum, Hydroteated Light

**Hazard pictograms** 



Signal word Danger

**Hazard statements** 

H220 Extremely flammable gas.
H222 Extremely flammable aerosol.

H229 Pressurized container: May burst if heated.
H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

#### **Precautionary statements**

Prevention

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing gas.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves.

Response

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P331 Do NOT induce vomiting.

P302 + P352 IF ON SKIN: Wash with plenty of water.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER/doctor if you feel unwell.
P332 + P313 If skin irritation occurs: Get medical advice/attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.

P377 Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

P381 Eliminate all ignition sources if safe to do so.

Storage

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**Supplemental label information** None known. **2.3. Other hazards** Combustible.

#### **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

**General information** 

Chemical name % CAS-No. / EC REACH Registration No. INDEX No. Notes No.

Distillates Petroleum, Hydroteated 60 - 70 64742-47-8 - 649-422-00-2

Light 265-149-8

Classification: DSD: Xn;R65

CLP: Asp. Tox. 1;H304, Skin Irrit. 2;H315, STOT SE 3;H336

#### List of abbreviations and symbols that may be used above

DSD: Directive 67/548/EEC. CLP: Regulation No. 1272/2008.

#: This substance has been assigned Union workplace exposure limit(s).

M: M-factor

PBT: persistent, bioaccumulative and toxic substance. vPvB: very persistent and very bioaccumulative substance.

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

**Composition comments** The full text for all R- and H-phrases is displayed in section 16.

#### **SECTION 4: First aid measures**

**General information** Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves.

4.1. Description of first aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON

CENTRE or doctor/physician if you feel unwell.

Skin contact Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get

medical advice/attention. Wash contaminated clothing before reuse.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

Call a physician or poison control centre immediately. Rinse mouth. Do not induce vomiting. If Ingestion

vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

4.2. Most important symptoms and effects, both acute and delayed

Aspiration may cause pulmonary oedema and pneumonitis. May cause drowsiness and dizziness.

Headache. Nausea, vomiting. Skin irritation. May cause redness and pain.

4.3. Indication of any immediate medical attention and special treatment needed Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

#### **SECTION 5: Firefighting measures**

General fire hazards Extremely flammable aerosol. Combustible.

5.1. Extinguishing media

Suitable extinguishing

media

Alcohol resistant foam. Powder. Dry chemicals. Carbon dioxide (CO2).

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture Contents under pressure. Pressurised container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters

Special protective equipment for firefighters

Special fire fighting procedures

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Use standard firefighting procedures and consider the hazards of other involved materials. Move Specific methods

containers from fire area if you can do so without risk. In the event of fire and/or explosion do not

breathe fumes.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. Use personal protection recommended in Section 8 of the SDS.

For emergency responders

Keep unnecessary personnel away. Use personal protection recommended in Section 8 of the SDS.

6.2. Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

Material name: A-151 (Aerosol) - ITW Pro Brands (EU)

04320, M04320 Version #: 02 Revision date: 05-October-2016 Issue date: 27-September-2015

#### 6.3. Methods and material for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Use water spray to reduce vapours or divert vapour cloud drift. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material.

Large Spills: Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Scoop up used absorbent into drums or other appropriate container. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use.

#### 6.4. Reference to other sections

Use personal protection recommended in Section 8 of the SDS. For waste disposal, see section

#### **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Pressurised container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Avoid breathing gas. Avoid contact with eyes, skin, and clothing. Avoid prolonged or repeated contact with skin. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

#### 7.2. Conditions for safe storage, including any incompatibilities

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Keep away from heat and sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

Not available. 7.3. Specific end use(s)

#### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

#### Occupational exposure limits

Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG)

Components	Туре	Value	Form
Distillates Petroleum, Hydroteated Light (CAS 64742-47-8)	TWA	5 mg/m3	Respirable aerosol fraction
		350 mg/m3	Vapor.
		50 ppm	Vapor.
Biological limit values	No biological exposure limits noted for the ingredient(s).		
Recommended monitoring procedures	Follow standard monitoring procedures.		
Derived no effect levels (DNELs)	Not available.		
Predicted no effect concentrations (PNECs)	Not available.		
8.2. Exposure controls			

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

#### Individual protection measures, such as personal protective equipment

**General information** Use personal protective equipment as required. Personal protection equipment should be chosen

according to the CEN standards and in discussion with the supplier of the personal protective

equipment.

Wear safety glasses with side shields (or goggles). Eye/face protection

Skin protection

- Hand protection Wear appropriate chemical resistant gloves. - Other Wear appropriate chemical resistant clothing.

**Respiratory protection** In case of insufficient ventilation, wear suitable respiratory equipment.

Material name: A-151 (Aerosol) - ITW Pro Brands (EU)

04320, M04320 Version #: 02 Revision date: 05-October-2016 Issue date: 27-September-2015

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

Hygiene measures When using do not smoke. Always observe good personal hygiene measures, such as washing

after handling the material and before eating, drinking, and/or smoking. Routinely wash work

clothing and protective equipment to remove contaminants.

**Environmental exposure** 

controls

Environmental manager must be informed of all major releases.

#### **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

**Appearance** 

**Physical state** Gas Aerosol **Form** 

Colour Clear water-white Characteristic. Odour Not determined Odour threshold Not available. Melting point/freezing point Not available. Initial boiling point and boiling 195 °C (383 °F)

range

Flash point 70,0 °C (158,0 °F) Tag closed cup

**Evaporation rate** < 0.1 BuAc Flammability (solid, gas) Flammable gas. Upper/lower flammability or explosive limits

Flammability limit - lower

0,6 % Estimated

Flammability limit - upper

20.4 % Estimated

(%)

< 0,1 mm Hg @ 20 °C Vapour pressure

Vapour density 6,1 (Air = 1)Relative density Not available.

Solubility(ies)

Solubility (water) Not soluble in water Not available. Solubility (other)

Partition coefficient > 1

(n-octanol/water)

> 194 °C (> 381,2 °F) **Auto-ignition temperature** 

**Decomposition temperature** Not available. < 3 mm<sup>2</sup>/s @ 25 °C **Viscosity Explosive properties** Not explosive. Oxidising properties Not oxidising

9.2. Other information

Heat of combustion > 30 kJ/g

Specific gravity 0,84 - 0,86 @ 20 °C

VOC 0 % per U.S State and Federal Consumer Product Regulations.

#### **SECTION 10: Stability and reactivity**

10.1. Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Material is stable under normal conditions. 10.2. Chemical stability

10.3. Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Strong oxidising agents. 10.5. Incompatible materials

Carbon oxides. 10.6. Hazardous

decomposition products

#### **SECTION 11: Toxicological information**

**General information** Occupational exposure to the substance or mixture may cause adverse effects. Information on likely routes of exposure

Inhalation May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be

harmful.

**Skin contact** Causes skin irritation.

**Eye contact** Direct contact with eyes may cause temporary irritation.

**Ingestion** Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious

chemical pneumonia.

**Symptoms** Aspiration may cause pulmonary oedema and pneumonitis. May cause drowsiness and dizziness.

Headache. Nausea, vomiting. Skin irritation. May cause redness and pain.

11.1. Information on toxicological effects

**Acute toxicity** May be fatal if swallowed and enters airways.

Components Species Test results

Distillates Petroleum, Hydroteated Light (CAS 64742-47-8)

Acute Dermal

LD50 Rabbit > 2000 mg/kg

Inhalation

Vapour

LC50 Rat > 4,5 mg/l, 4 Hours

Oral

LD50 Rat > 5000 mg/kg

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

irritation

Direct contact with eyes may cause temporary irritation.

**Respiratory sensitisation** Not a respiratory sensitizer.

**Skin sensitisation** This product is not expected to cause skin sensitisation.

**Germ cell mutagenicity**No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

Hungary. 26/2000 EüM Ordinance on protection against and preventing risk relating to exposure to carcinogens at work (as amended)

umonaca

Not listed.

**Reproductive toxicity**This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

May cause drowsiness and dizziness.

Specific target organ toxicity -

repeated exposure

Not classified.

repeated expectate

**Aspiration hazard** May be fatal if swallowed and enters airways.

Mixture versus substance

information

No information available.

Other information None known.

**SECTION 12: Ecological information** 

**12.1. Toxicity** The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components Species Test results

Distillates Petroleum, Hydroteated Light (CAS 64742-47-8)

Aquatic

Fish LC50 Rainbow trout, donaldson trout 2,9 mg/l, 96 hours

(Oncorhynchus mykiss)

**12.2. Persistence and**No data is available on the degradability of this product.

degradability

12.3. Bioaccumulative potential

Partition coefficient n-octanol/water (log Kow)

A-151 (Aerosol) > 1

Bioconcentration factor (BCF) Not available.

Material name: A-151 (Aerosol) - ITW Pro Brands (EU)
04320, M04320 Version #: 02 Revision date: 05-October-2016 Issue date: 27-September-2015

12.4. Mobility in soil No data available.12.5. Results of PBT Not available.

and vPvB assessment

**12.6. Other adverse effects** None known.

#### **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Residual waste Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal. Do not re-use empty containers.

**EU waste code**The Waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Disposal methods/information Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents

under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance

 $with \ local/regional/national/international\ regulations.$ 

**Special precautions** Dispose in accordance with all applicable regulations.

#### **SECTION 14: Transport information**

#### **ADR**

**14.1. UN number** UN1950

**14.2. UN proper shipping** Aerosols, flammable

name

14.3. Transport hazard class(es)

Class 2.1 Subsidiary risk -Label(s) 2.1

Hazard No. (ADR) Not available.

Tunnel restriction code D

**14.4. Packing group** Not applicable.

14.5. Environmental hazards No.

**14.6. Special precautions** Read safety instructions, SDS and emergency procedures before handling.

for user

**RID** 

**14.1. UN number** UN1950

**14.2. UN proper shipping** Aerosols, flammable

name

14.3. Transport hazard class(es)

Class 2.1 Subsidiary risk -Label(s) 2.1

**14.4. Packing group** Not applicable.

14.5. Environmental hazards No.

14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling.

for user

ADN

**14.1. UN number** UN1950

**14.2. UN proper shipping** Aerosols, [flammable]

name

14.3. Transport hazard class(es)

Class 2.1 Subsidiary risk -Label(s) 2.1

**14.4. Packing group** Not applicable.

14.5. Environmental hazards No.

**14.6. Special precautions** Read safety instructions, SDS and emergency procedures before handling.

for user

IATA

**14.1. UN number** UN1950

14.2. UN proper shipping Aerosols, flammable

name

#### 14.3. Transport hazard class(es)

Class 2.1 Subsidiary risk -

**14.4. Packing group** Not applicable.

**14.5. Environmental hazards** No. **ERG Code** 10L

**14.6. Special precautions** Read safety instructions, SDS and emergency procedures before handling.

for user

**IMDG** 

**14.1. UN number** UN1950 **14.2. UN proper shipping** AEROSOLS

name

14.3. Transport hazard class(es)

Class 2 Subsidiary risk -

**14.4. Packing group** Not applicable.

14.5. Environmental hazards

14.6. Special precautions Read saf

for user

Read safety instructions, SDS and emergency procedures before handling.

14.7. Transport in bulk according to Annex II of Marpol

and the IBC Code

ADN; ADR; IATA; IMDG; RID

Not listed.



#### **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended Not listed.

Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended

Not applicable.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA Not listed.

#### **Authorisations**

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended Not listed.

#### Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended Not listed.

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.

Not listed

#### Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

Not listed.

Other regulations The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP

Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation

(EC) No 1907/2006, as amended.

National regulations Follow national regulation for work with chemical agents. Young people under 18 years old are not

allowed to work with this product according to EU Directive 94/33/EC on the protection of young

people at work, as amended.

15.2. Chemical safety

assessment

No Chemical Safety Assessment has been carried out.

#### **SECTION 16: Other information**

List of abbreviations Not available.

References Not available.

Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

Full text of any statements or R-phrases and H-statements under Sections 2 to 15

R12 Extremely flammable. R38 Irritating to skin.

R65 Harmful: may cause lung damage if swallowed. R67 Vapours may cause drowsiness and dizziness. H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

Revision information

This document has undergone significant changes and should be reviewed in its entirety.

**Training information** 

Follow training instructions when handling this material.

Disclaimer

ITW Pro Brands cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.